


FLEXILED XF2499

24V DC Flexible LED strip with a close pitch of 99 LEDs per meter for reduced spotting effects. Maximum power consumption of 20W per meter with a lumen output of 2300lm per meter. Supplied in 6 meter reels with 3M adhesive backing, cuttable at 60mm intervals for quick and easy installation.



Specifications

Voltage	24V DC
Wattage	20W per meter
SMD Lumens	2300 lm per meter
CRI	80+
Colour Deviation	SDCM \leq 3
Lifetime	50,000hrs
LED Pitch	99 LEDs per meter
Cutting Increment	60mm (6 LEDs)
Reel Length	6m
Adhesive Backing	3M 300LSE
Copper Content	2oz PCB

Extrusion Options

A variety of extrusion options are available for the Flexiled range, these aluminium extrusion profiles suit a wide range of lighting applications and mounting options.



Product

XF2499

CCT

- 2700K 2.7
- 3000K 3
- 4000K 4
- 5000K 5

Length

Length in mm XX

XF2499

3

5000

XF24993-5000



TREND
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au