




## LED SPOT XTN15E

15 Watts / 2300+ Lumens / 94+ CRI

15W Track mounted miniature LED spotlight featuring a 2300+ lumen ceramic Nichia LED with a high efficiency collimating lens and low glare honeycomb diffuser. Available in 2700K, 3000K, 3500K and 4000K colour temperature options in a 94+ CRI with an R9 of 50+. Supplied with 3-circuit track adaptor with integral track mounted driver.

Also available with Nichia's award winning Optisolis™ LED.



90°

350°

System Power 16.8W

LED Power 15W

IP Rating IP20

Tilt-Angle 90°

Rotation 350°

Weight 685g

	2700K	3000K	3500K	4000K
COB Lumen Output	2235 lm	2270 lm	2290 lm	2310 lm
Total Luminous Flux	1587 lm	1609 lm	1626 lm	1646 lm
Efficacy	97.9 lm/W 4000K			Lifetime 60,000hrs (L80 B10)
Dimming	Optional: Dali			
Input Voltage	100V - 240V AC 50/60 Hz		Protection Thermal and Short Circuit	Power Factor > 0.95



Concealed Track Mounted Driver

Product	CCT	Light Source	Beam Angle	Trim Colour	Driver
XTN15E	2700K 2.7	94+ CRI	Wide Beam WB	White W	none
	3000K 3	Optisolis* O	Medium Beam MB	Black B	DALI*
	3500K 3.5		Narrow Beam NB		
	4000K 4				
XTN15E	3		WB	W	

XTN15E3-WB-W

\* Optional



**TREND**  
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020  
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au