



MINILED XDQ10


10.5 Watts / 1390 Lumens / 90+ CRI




10 Watt Adjustable low glare LED downlight featuring a single COB LED design available in 2700K, 3000K, 4000K and 5000K colour temperature options in 90+ CRI or 2700K, 3000K and 4000K VIVID options. The Miniled range is supplied with remote driver.

System Power 11.7W
LED Power 10.5W
IP Rating IP20

Cut-Out 76mm
Weight 280g



Removable trim insert



	2700K	3000K	4000K	5000K	VIVID	2700K	3000K	4000K
COB Lumen Output	1300 lm	1335 lm	1390 lm	1410 lm	VIVID	1080 lm	1120 lm	1150 lm
Total Luminous Flux	463 lm	498 lm	533 lm	553 lm		385 lm	399 lm	410 lm

Efficacy	45.55 lm/W 4000K Narrow Beam	Lifetime	50,000hrs (L80)
Dimming	Leading + Trailing Edge	Optional: Dali	1-10v
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit
		Power Factor	> 0.95

Product	CCT	Light Source	Beam Angle	Trim Colour	Driver
XDQ10	2700K 2.7	90+ CRI	Narrow Beam NB	White W	Leading + Trailing
	3000K 3	VIVID* V		Black B	DALI*
	4000K 4			Silver S	1-10v*
	5000K 5				
XDQ10	3		NB	W	

XDQ103-NB-W

* Optional



TREND
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au