




SURFACE LED XSO10

10 Watts / 1390 Lumens / 90+ CRI

Surface mounted compact LED manufactured with a single high output 10W LED with a high colour rendering index of 90+ . Comprehensive range of accessories allow for versatile illumination options covering a variety of lighting demands. Integrated heatsink provides effective thermal management ensuring high output and long lifespan. Supplied with an integral driver.



| | | | |
|--------------|-------|--------|------|
| System Power | 11.7W | Weight | 525g |
| LED Power | 10W | | |
| IP Rating | IP20 | | |

| | 2700K | 3000K | 4000K |
|---------------------|---------|---------|---------|
| COB Lumen Output | 1300 lm | 1335 lm | 1390 lm |
| Total Luminous Flux | 998 lm | 1032 lm | 1079 lm |

| | | | | | |
|---------------|----------------------------|------------|---------------------------|--------------|--------|
| Efficacy | 92.2 2lm/W 4000K Wide Beam | Lifetime | 50,000hrs (L80) | | |
| Input Voltage | 100V - 240V AC 50/60 Hz | Protection | Thermal and Short Circuit | Power Factor | > 0.95 |



| Product | CCT | | Beam Angle | | Trim Colour | | Optional Accessories | |
|---------|-------|-----|-------------|----|-------------|---|----------------------|----|
| XSO10 | 2700K | 2.7 | Wide Beam | WB | White | W | Standard Ring | |
| | 3000K | 3 | Medium Beam | MB | Black | B | Honeycomb Lens | HL |
| | 4000K | 4 | Narrow Beam | NB | | | Cross Louvre | CL |
| | | | | | | | Snoot | SR |
| | | | | | | | Eye Snoot | ER |
| | | | | | | | Wallwash Ring | WR |
| | | | | | | | Barn Door | BD |
| XSO10 | 3 | | WB | | W | | | |

XSO103-WB-W-ER

* Optional