



# Wireguard ZBW

20 Watts / 2500 Lumens / 85+ CRI

40 Watts / 5500 Lumens / 85+ CRI

Surface Mounted linear LED wire guard batten manufactured using Japanese based die's featuring 150lm/w technology. Powdercoated body with acrylic diffuser for smooth uniform light distribution and steel wire guard for increased impact resistance. Internally mounted 4mm Terminal block included for ease of installation.

Available as a 4 hour Maintained or Non-Maintained battery backup emergency system.

Input Voltage 240V

Lamp Type LED

IP Rating IP20

Weight 1300g

ZBW224

System Power 20.0W

LED Power 18W

ZBW444

System Power 44.9W

LED Power 40W

## ZBW Specifications

|                     | ZBWP224                                  | ZBW444   |
|---------------------|------------------------------------------|----------|
| COB Lumen Output    | 2500 lm                                  | 5500 lm  |
| Total Luminous Flux | 2194 lm                                  | 4906 lm  |
| Efficacy            | 110 lm/W                                 | 109 lm/W |
| Lifetime            | 50,000hrs (L70)                          |          |
| Power Factor        | > 0.96                                   |          |
| Input Voltage       | 220V - 240V AC 50/60 Hz                  |          |
| Protection          | Thermal and Short Circuit                |          |
| Dimming             | DALI* 1-10v* Available on request        |          |
| Emergency Systems   | Optional 4 hour Battery Backup available |          |

## ZBW Dimensions



## ZBW Trim Colours



White

## ZBW Order Code



**TREND**  
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020  
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au