

Linear ZDWO36

36W IP65 & IK10 Rated Linear Light with Opal Diffuser



ZDWO36 online

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Driver |
|--------------|--------------------|--------------------|----------------|-------------|-------------------|
| ZDWO36 | 3 (3000K) | (CRI 90+ Standard) | VW (Very Wide) | W (White) | ND (Non-dimmable) |
| | 4 (4000K) | | | B (Black) | DALI DALI |

Order Code ZDW0364-VW-B-ND




To configure this linear light, please visit trendlighting.com.au/product/linear-ZDWO36

Physical Characteristics

| Trim Colour | White Black |
|--------------------|-------------------|
| Dimensions (LxWxH) | 1135 x 65 x 75 mm |

Dimensions (mm)



Product Features

- Modular LED linear profile with opal diffuser for smooth light beam distribution
- IP65 & IK10 rated suitable for high-humidity environments
- Flexible mounting options available: suspended, ceiling-mounted, or wall-mounted
- Comes in fixed lengths, but can be linked into a continuous run using a 180° connector and cable, or an IP65 cable
- Also available in 45W (ZDWO45)
- CRI 90+ available in 3000K and 4000K options

Product Attributes











| Technical Characteristics | Based on ZDWO364-VW-B-NE | | |
|----------------------------------|---------------------------|--|--|
| LED Type | SMD | | |
| Luminous Flux | 3636 lm | | |
| Efficacy | 101 lm/W | | |
| Colour Temperature | 3000K 4000K | | |
| Colour Technology | CRI 90+ | | |
| Colour Deviation | SDCM ≤ 3 | | |
| Lifetime | 50,000 hours (L70) | | |
| Beam Angle | Very Wide | | |
| System Power | 36W Typical | | |
| Driver Model | Trend DR-ZDWO36 (Non-dim) | | |
| Input | 220-240V AC 50/60 Hz | | |
| Power Factor | >0.90 | | |
| Protection | OVP, OTP, OCP, SCP, OPP | | |
| Dimming | Non-dimmable DALI | | |

General Characteristics

| Category | Linears & Battens | | |
|--------------------|-----------------------------|--|--|
| Family | Linear | | |
| Surface | Ceiling Wall | | |
| Mounting | Surface Mounted Suspended | | |
| Ingress Protection | IP65 | | |
| Impact Resistance | IK10 | | |
| | | | |



Linear ZDWO36

Scan to explore ZDWO36 online

36W IP65 & IK10 Rated Linear Light with Opal Diffuser

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Driver |
|--------------|--------------------|--------------------|----------------|-------------|-------------------|
| ZDW036 | 3 (3000K) | (CRI 90+ Standard) | VW (Very Wide) | W (White) | ND (Non-dimmable) |
| | 4 (4000K) | | | B (Black) | DALI DALI |

Order Code ZDW0364-VW-B-ND

To configure this linear light, please visit

trendlighting.com.au/product/linear-ZDWO36

Trim Colour







Accessories



Surface Mount Kit



Wall Mount Kit



Suspension Kit



180° Connector & Cable



IP65 AC Cable