



Scan to explore  
XSO20 online

# Surface XSO20

20W Surface Mounted Compact Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
XSO20	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	BD (Barn Door)	DALI (DALI)
	3 (3000K)		MB (Medium)	B (Black)	CL (Cross Louvre)	110V (1-10V)
	4 (4000K)				ER (Eye Snoot)	ND (Non-dimmable)
						HL (Honeycomb Lens)
				SR (Snoot)		
					WR (Wallwash Ring)	

Order Code **XSO204-MB-B-ND**

\* Optional accessories



## Product Features

- Surface mounted compact LED downlight, manufactured with an aluminium body and powder coat finish
- Available with a comprehensive range of accessories, catering for a variety of lighting demands
- CRI 90+ available in 2700K, 3000K and 4000K CCT options
- Supplied with an integral driver

To configure this downlight, please visit  
[trendlighting.com.au/product/surface-XSO20](http://trendlighting.com.au/product/surface-XSO20)


## Product Attributes



## Physical Characteristics

Trim Colour	White   Black
Dimensions	Ø83 x 183 (H) mm
Weight	867 g

## Dimensions (mm)



## Technical Characteristics

Based on XSO204-MB-B-ND

LED Power	20W
LED Type	COB
Lumen Output	3132 lm
Luminous Flux	2527 lm
Efficacy	108.92 lm/W
Colour Temperature	2700K   3000K   4000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 2
Lifetime	50,000 hours (L80)
Beam Angle	Narrow   Medium
System Power	23.2W Typical
Driver Model	Trend 150417-500 (Non-dim)
Input	220-240V AC 50/60 Hz
Output	25-42V DC 500mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	DALI   1-10V   Non-dimmable

## General Characteristics

Category	Downlights
Family	Surface
Surface	Ceiling
Mounting	Surface Mounted
Ingress Protection	IP20



Scan to explore  
XSO20 online

# Surface XSO20

20W Surface Mounted Compact Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
<b>XSO20</b>	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	BD (Barn Door)	DALI (DALI)
	3 (3000K)		MB (Medium)	B (Black)	CL (Cross Louvre)	110V (1-10V)
	4 (4000K)				ER (Eye Snoot)	ND (Non-dimmable)
					HL (Honeycomb Lens)	
					SR (Snoot)	
					WR (Wallwash Ring)	

Order Code **XSO204-MB-B-ND**


\* Optional accessories

To configure this downlight, please visit  
[trendlighting.com.au/product/surface-XSO20](http://trendlighting.com.au/product/surface-XSO20)

## Trim Colour



W  
White Trim



B  
Black Trim

## Accessories \*



BD  
Barn Door



CL  
Cross Louvre



ER  
Eye Snoot



HL  
Honeycomb Lens



SR  
Snoot



WR  
Wallwash Ring