



Scan to explore  
XSR2515-IP65 online

# Surface XSR2515-IP65

15W IP65 Rated Surface Mounted Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
<b>XSR2515-IP65</b>	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	WI (White)	TE (Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)		SI (Silver)	110V (1-10V)
	4 (4000K)				GI (Gold)	

Order Code **XSR2515-IP65-4-WB-B-BI-TE**



To configure this downlight, please visit  
[trendlighting.com.au/product/surface-XSR2515-IP65](http://trendlighting.com.au/product/surface-XSR2515-IP65)

## Product Features

- Surface mounted LED downlight with sealed body providing an IP65 rating
- Sealed face with silicone gasket for added ingress protection
- Designed with no visible mounting screws providing a cleaner look with a large integral pin fin heatsink for excellent thermal management
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with an integral driver


## Product Attributes



## Physical Characteristics

Trim Colour	White   Black
Insert Colour	White   Black   Silver   Gold
Dimensions	Ø110 x 215 (H) mm
Weight	1490 g

## Dimensions (mm)



## Technical Characteristics

Based on XSR2515-IP65-4-WB-B-BI-TE

LED Power	15W
LED Type	COB
Lumen Output	2004 lm
Luminous Flux	1593 lm
Efficacy	89.49 lm/W
Colour Temperature	2700K   3000K   3500K   4000K
Colour Technology	CRI 90+   CRI 93+ VIVID   CRI 97+
Colour Deviation	SDCM ≤ 2
Lifetime	50,000 hours (L80)
Beam Angle	Narrow   Medium   Wide

System Power	17.8W Typical
Driver Model	Trend 150077-350 (T/E)
Input	220-240V AC 50/60 Hz
Output	26-43V DC 350mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Trailing Edge   DALI   1-10V

## General Characteristics

Category	Downlights
Family	Surface
Surface	Ceiling
Mounting	Surface Mounted
Ingress Protection	IP65



Scan to explore  
XSR2515-IP65 online

# Surface XSR2515-IP65

15W IP65 Rated Surface Mounted Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
<b>XSR2515-IP65</b>	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	WI (White)	TE (Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)		SI (Silver)	110V (1-10V)
	4 (4000K)				GI (Gold)	

Order Code **XSR2515-IP65-4-WB-B-BI-TE**

To configure this downlight, please visit  
[trendlighting.com.au/product/surface-XSR2515-IP65](http://trendlighting.com.au/product/surface-XSR2515-IP65)

## Trim Colour




W  
White Trim



B  
Black Trim

## Insert Colour




WI  
White Insert



BI  
Black Insert



SI  
Silver Insert



GI  
Gold Insert