



Scan to explore
ZBB22 online


Diffused Batten ZBB22

14W Surface Mounted Diffused Batten

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver	Emergency Kit*
ZBB22	2.7 (2700K)	(CRI 90+ Standard)	VW (Very Wide)	W (White)	ND (Non-dimmable) DALI (DALI) 110V (1-10V)	EMB (Maintained Backup)
	3 (3000K)					ENB (Non-maintained Backup)
	4 (4000K)					
	5 (5000K)					

Order Code **ZBB224-VW-W-ND**

* Optional emergency kit



Product Features


- Surface mounted diffused LED batten with powder coated body and acrylic prismatic diffuser for smooth uniform light distribution
- Optional battery backup kit available in maintained or non-maintained variants, meeting AS/NZS 2293 compliance
- CRI 90+ available in 2700K, 3000K, 4000K and 5000K CCT options
- Supplied with an integral driver and internally mounted 4mm² terminal block for easy installation

To configure this batten, please visit
trendlighting.com.au/product/diffused-batten-ZBB22

Physical Characteristics

Trim Colour	White
Dimensions (LxWxH)	595 x 95 x 83 mm
Weight	2 kg

Dimensions (mm)



Product Attributes



Technical Characteristics

Based on ZBB224-VW-W-ND

LED Power	14W
LED Type	SMD
Lumen Output	2232 lm
Luminous Flux	1560 lm
Efficacy	97.5 lm/W
Colour Temperature	2700K 3000K 4000K 5000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L80 B10)
Beam Angle	Very Wide
System Power	16W Typical
Driver Model	Trend 150232 (Non-dim)
Input	220-240V AC 50/60 Hz
Output	24V DC 2.08A
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Non-dimmable DALI 1-10V

General Characteristics

Category	Linears & Battens
Family	Diffused Batten
Surface	Ceiling
Mounting	Surface Mounted
Ingress Protection	IP20



Scan to explore
ZBB22 online

Diffused Batten ZBB22

14W Surface Mounted Diffused Batten

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver	Emergency Kit *
ZBB22	2.7 (2700K)	(CRI 90+ Standard)	VW (Very Wide)	W (White)	ND (Non-dimmable) DALI (DALI) 110V (1-10V)	EMB (Maintained Backup)
	3 (3000K)					ENB (Non-maintained Backup)
	4 (4000K)					
	5 (5000K)					

Order Code **ZBB224-VW-W-ND**

* Optional emergency kit

To configure this batten, please visit
trendlighting.com.au/product/diffused-batten-ZBB22

Trim Colour



W
White Trim

Emergency Kits *

EMB
Emergency Kit with Maintained Backup

- Illuminated all the time for safety but has the capacity to be switched on and off
- Continues to illuminate at a lower-level in the event of loss of power using its battery backup supply

ENB
Emergency Kit with Non-maintained Backup

- Only illuminates in the event of a loss of power
- When power fails, the fixture switches on using its battery backup supply