

Midiled XRA10

10W Recessed Adjustable Downlight



Scan to explore XRA10 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XRA10	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	WI (White) BI (Black) SI (Silver) GI (Gold)	LT (Leading & Trailing Edge) DALI (DALI) 110V (1-10V)

Order Code XRA104-MB-W-WI-LT




To configure this downlight, please visit trendlighting.com.au/product/midiled-XRA10

Physical Characteristics

Trim Colour	White Black			
Insert Colour	White Black Silver Gold			
Tilt Angle	45°			
Rotation	355°			
Dimensions	Ø92 x 125 (H) mm			
Spring Height	24 mm			
Cutout	Circular 84 mm			
Weight	410 g			

Dimensions (mm)





Product Features

- Recessed adjustable LED downlight with configurable inserts, providing versatility in lighting and aesthetic design
- Featured with 355° rotation and 45° tilting capabilities, allowing for directional adjustment in a variety of lighting applications
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes













Technical Characteristics	Based on XRA104-MB-W-WI-L1			
LED Power	10W			
LED Type	COB			
Lumen Output	1368 lm			
Luminous Flux	845 lm			
Efficacy	72.22 lm/W			
Colour Temperature	3000K 4000K			
Colour Technology	CRI 90+			
Colour Deviation	SDCM ≤ 2			
Lifetime	50,000 hours (L80)			
Beam Angle	Medium			
System Power	11.7W Typical			
Driver Model	Trend 150218-300 (L&T)			
Input	180-265V AC 50/60 Hz			
Output	30-42V DC 300mA			
Power Factor	>0.93			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Leading & Trailing Edge DALI 1-10V			
General Characteristics				
Category	Downlights			
Family	Midiled			
Surface	Ceiling			
Mounting	Recessed			
Insulation Contact	Non-IC			
Ingress Protection	IP20			



Midiled XRA10



10W Recessed Adjustable Downlight


Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XRA10	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	WI (White) BI (Black) SI (Silver) GI (Gold)	LT (Leading & Trailing Edge) DALI (DALI) 110V (1-10V)

Order Code XRA104-MB-W-WI-LT

To configure this downlight, please visit

trendlighting.com.au/product/midiled-XRA10

Trim Colour






W White Trim

Black Trim


Insert Colour








Black Insert



Silver Insert



GI Gold Insert