

# Panel ZPM20

### 20W Recessed Square Panel Light



ZPM20 online

\* Optional accessories

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
ZPM20	3 (3000K) 4 (4000K)	(CRI 80+ Standard)	UW (Ultra Wide)	W (White)	PR (Plaster Recessing Kit) SM (Surface Mounting Kit)	ND (Non-dimmable) DALI (DALI)
					SP (Suspension Kit)	

Order Code ZPM204-UW-W-ND




To configure this panel, please visit trendlighting.com.au/product/panel-ZPM20

### **Physical Characteristics**

Trim Colour	White			
Dimensions (LxWxH)	595 x 595 x 12 mm			
Weight	2.35 kg			

### **Dimensions (mm)**



### **Product Features**

- Square LED panel light known for its thin profile and high performance
- Designed with powder coated extruded aluminium frame with low glare and high transparency microprismatic diffuser
- Can be configured with different mounting kits suspended, surface mounted and plaster recessed
- Suitable for mounting in metric T-Bar ceiling applications
- CRI 80+ available in 3000K and 4000K options
- Supplied with a remote driver for easy installation

### **Product Attributes**



Technical Characteristics	Based on ZPM204-UW-W-ND			
LED Power	20W			
LED Type	SMD			
Lumen Output	2950 lm			
Luminous Flux	2330 lm			
Efficacy	104.02 lm/W			
Colour Temperature	3000K   <b>4000K</b>			
Colour Technology	CRI 80+			
Colour Deviation	SDCM ≤ 2			
Lifetime	50,000 hours (L70)			
Beam Angle	Ultra Wide			
System Power	22.4W Typical			
Driver Model	Trend 150020-700 (Non-dim)			
Input	180-265V AC 50/60 Hz			
Output	30-40V DC 700mA			
Power Factor	>0.90			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Non-dimmable   DALI			
General Characteristics				
Category	Panels & Troffers			
<b>F</b> :				

Category	Fallels & Hollels
Family	Panel
Surface	Ceiling
Mounting	Recessed   Surface Mounted
	Suspended
Insulation Contact	Non-IC
Ingress Protection	IP40



# Panel ZPM20

## 20W Recessed Square Panel Light



ZPM20 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
ZPM20	3 (3000K) 4 (4000K)	(CRI 80+ Standard)	UW (Ultra Wide)	W (White)	PR (Plaster Recessing Kit) SM (Surface Mounting Kit) SP (Suspension Kit)	ND (Non-dimmable) DALI (DALI)


Order Code ZPM204-UW-W-ND

\* Optional accessories

To configure this panel, please visit

trendlighting.com.au/product/panel-ZPM20

### Trim Colour



#### W White Trim

## Accessories \*



PR Plaster Recessing Kit



SM Surface Mounting Kit



SP Suspension Kit