

Surface XSO10

10W Surface Mounted Compact Downlight



Scan to explore XSO10 online

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Accessories * | Driver |
|--------------|--------------------|--------------------|-------------|-------------|---------------------|-------------------|
| XSO10 | 3 (3000K) | (CRI 90+ Standard) | NB (Narrow) | W (White) | BD (Barn Door) | DALI (DALI) |
| | 4 (4000K) | | MB (Medium) | B (Black) | CL (Cross Louvre) | 110V (1-10V) |
| | | | | | ER (Eye Snoot) | ND (Non-dimmable) |
| | | | | | HL (Honeycomb Lens) | |
| | | | | | SR (Snoot) | |
| | | | | | WR (Wallwash Ring) | |

Order Code XSO104-MB-B-ND * Optional accessories




To configure this downlight, please visit trendlighting.com.au/product/surface-XSO10

Physical Characteristics

| Trim Colour | White Black | | | |
|-------------|------------------|--|--|--|
| Dimensions | Ø60 x 157 (H) mm | | | |
| Weight | 424 g | | | |

Dimensions (mm)



Product Features

- Surface mounted compact LED downlight, manufactured with an aluminium body and powder coat finish
- Available with a comprehensive range of accessories, catering for a variety of lighting demands
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with an integral driver

Product Attributes









| Technical Characteristics | Based on XSO104-MB-B-ND |
|---------------------------|-------------------------|
| LED Power | 10W |
| LED Type | COB |
| Lumen Output | 1450 lm |
| Luminous Flux | 1047 lm |
| Efficacy | 89.49 lm/W |
| Colour Temperature | 3000K 4000K |
| Colour Technology | CRI 90+ |
| Colour Deviation | SDCM ≤ 2 |
| Lifetime | 50,000 hours (L80) |
| Beam Angle | Narrow Medium |
| | |

| System Power | 11.7W Typical |
|--------------|-----------------------------|
| Driver Model | Trend 150417-500 (Non-dim) |
| Input | 220-240V AC 50/60 Hz |
| Output | 25-42V DC 500mA |
| Power Factor | >0.90 |
| Protection | OVP, OTP, OCP, SCP, OPP |
| Dimming | DALI 1-10V Non-dimmable |

General Characteristics

| Category | Downlights |
|--------------------|-----------------|
| Family | Surface |
| Surface | Ceiling |
| Mounting | Surface Mounted |
| Ingress Protection | IP20 |



Surface XSO10

10W Surface Mounted Compact Downlight



Scan to explore XSO10 online

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Accessories * | Driver |
|--------------|------------------------|--------------------|----------------------------|------------------------|---|--|
| XS010 | 3 (3000K) 4 (4000K) | (CRI 90+ Standard) | NB (Narrow) MB (Medium) | W (White) B (Black) | BD (Barn Door) CL (Cross Louvre) ER (Eye Snoot) HL (Honeycomb Lens) SR (Snoot) WR (Wallwash Ring) | DALI (DALI) 110V (1-10V) ND (Non-dimmable) |

Order Code XS0104-MB-B-ND * Optional accessories

To configure this downlight, please visit

 $\underline{trendlighting.com.au/product/surface-XSO10}$

Trim Colour





White Trim

Black Trim

Accessories *



Barn Door



CL Cross Louvre



Eye Snoot



HL Honeycomb Lens



SR Snoot



WR **Wallwash Ring**