

Unoled TL10

10 Watt Recessed Compact Tricolour Downlight

Recessed fixed SMD LED downlight designed with a slim profile and extra wide light beam distribution. Manufactured with an aluminium body and finished in durable white powder coating.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white), and 5700K (daylight). Supplied with a remote flicker free Trailing Edge dimmable driver.



Product	CCT	Trim Colour	Driver	Order Code
TL10	Tricolour	White Trim	Trailing Edge	TL10-TRI-W-TE

Spec	ific	atio	ns

- poormoutions			
Trim Colour Options	White		
Cutout	Ø85-95 mm		
Dimensions	Ø104 x 45 (H) mm		
Weight	170 g		
LED Power	10W		
LED Type	SMD		
Lumen Output	1000 lm		
CCT Technology	Tri-colour Selectable		
Colour Temperature (CCT)	3000K, 4000K, 5700K		
Colour Rendering	CRI 80+		
Lifetime	50,000 hours (L70)		
Beam Angle	Wide 120°		
System Power	11.7W Typical		
Efficacy	Up to 87 lm/W		
Input	200-240V AC 50 Hz		
Power Factor	>0.95		
Dimming	Trailing Edge		
Driver Type	Remote, Flicker Free		
Connection Type	Flex and Plug		
Ingress Protection	IP44		
Insulation Rating	IC-4 AS/NZS 60598.2.2		
IEC Protection	Class II		
Warranty	3 Years		



















