

Wall WRD7

5W IP65 Rated Classic Uni-directional Wall Light



Scan to explore WRD7 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
WRD7	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)	ND (Non-dimmable)
	4 (4000K)			B (Black)	

Order Code WRD74-WB-B-ND




To configure this wall light, please visit trendlighting.com.au/product/wall-WRD7

Physical Characteristics

Trim Colour	White Black		
Dimensions	Ø60 x 121 (H) mm		
Weight	765 g		

Dimensions (mm)



Product Features

- Surface mounted IP65 rated sleek wall light in a uni-directional light configuration
- Manufactured from a stainless steel body and powder coat finish
- Sealed safety glass lens for ingress protection
- Characterised by its black print insert, allowing for seamless integration with contemporary architecture
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with integral driver

Product Attributes











Technical Characteristics	Based on WRD74-WB-B-ND		
LED Power	5.25W		
LED Type	COB		
Lumen Output	875 lm		
Luminous Flux	514 lm		
Efficacy	73.43 lm/W		
Colour Temperature	3000K 4000K		
Colour Technology	CRI 90+		
Colour Deviation	SDCM ≤ 3		
Lifetime	50,000 hours (L80)		
Beam Angle	Wide		
System Power	7W Typical		
Driver Model	Trend DR-WRD7 (Non-dim)		
Input	100-240V AC 50/60 Hz		
Power Factor	>0.95		
Dimming	Non-dimmable		

General Characteristics

Category	Exterior	
Family	Wall	
Surface	Wall	
Mounting	Surface Mounted	
Ingress Protection	IP65	



Wall WRD7



Scan to explore WRD7 online

5W IP65 Rated Classic Uni-directional Wall Light

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
WRD7	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)	ND (Non-dimmable)
	4 (4000K)			B (Black)	

Order Code WRD74-WB-B-ND

To configure this wall light, please visit

trendlighting.com.au/product/wall-WRD7

Trim Colour





W White Trim

Black Trim